

**SENSIT<sup>®</sup> HXG-3**  
COMBUSTIBLE GAS LEAK DETECTOR



**SENSIT<sup>®</sup> HXG-3**  
makes finding gas leaks fast and easy!

MADE IN USA

# SENSIT<sup>®</sup> HXG-3

## COMBUSTIBLE GAS LEAK DETECTOR

**SENSIT<sup>®</sup> HXG-3** is an advanced state-of-the-art combustible gas leak detector capable of sensing many combustible gases such as methane, propane and natural gas.

The backlit LCD display shows percent lower explosive limit (LEL) and part-per million (ppm) readings simultaneously for accurate leak detection and analysis. Audible and visual alarms warn of potential hazardous conditions.

### Pinpoint Leaks

Leaks can easily be pinpointed by using an audible tick rate. The sensor is located at the end of a flexible gooseneck to easily reach areas where leaks may be suspected.

### Data Save

A Data Save feature allows you to save data during any investigation.

### HXG-3 Standard Features

- Displays LEL and PPM
- Infrared Downloading
- Long-life, Low-Cost Sensor
- Simple Calibration



### INDUSTRY USERS

Natural Gas Companies  
Propane Suppliers  
Electric Companies  
Safety Engineers  
Fire and Police  
Emergency Vehicles  
Appliance Repair  
Plant Maintenance  
Plumbing Contractors  
Marine Operations  
Heating and Air Conditioning  
Municipalities  
Mobile Home Parks  
Apartment Buildings

### APPLICATIONS

Confined Space Monitoring  
Vessel Testing  
Manhole Entry  
Vault Entry  
Leak Detection  
Leak Pinpointing  
Pipeline Purging

### PARTIAL LIST OF GASES SENSED\*

Acetone	Industrial Solvents
Alcohol	Jet Fuel - 2610
Ammonia	Lacquer Thinner
Butane	Methane
Ethylene Oxide - 2610	Natural Gas
Gasoline	Propane
Halon	Refrigerants
Hydrogen	

\*Contact Sensit Technologies for more info.



**TO OPERATE:**

- 1. Press Power**
- 2. Wait 45 Seconds for Automatic Zeroing**
- 3. Begin to Use**

Patented

**SENSOR SPECIFICATIONS**

TYPE	RESOLUTION	RANGE	ACCURACY
PPM*	1 or 10ppm	0-50,000 ppm	±10%
LEL	0.1%	0-100% LEL	±10%

\*PPM Optional

**PRODUCT SPECIFICATIONS**

- Size: 11.5" x 3" x 2.2" (29.21 x 7.62 x 5.89 cm)
- Weight: 1.2 lb. (0.54 kg)
- Operational Temp: -4 to 122° F (-20 to 50° C)
- Battery Life: Alkaline: Approximately 25 hrs. Continuous



**STANDARD KIT**

- Hard Carrying Case
- 3 "C" Batteries
- Wrist Strap
- Instruction Manual

**KIT OPTIONS**

- Optional PPM
- Probe Assembly
- Printer
- PC Interface
- Calibration Kit

**OPTIONAL FEATURES**

- Internal Pump (HXG-3P):**
- Provides Faster Response
- Provides Better Sensor Protection



SENSIT® HXG-3 instruments are approved UL913, For Class 1, Division 1, Groups C, D, T3 hazardous locations when used with Duracell MN1400BK batteries or equivalent alkaline batteries.

## SENSIT HXG-3 ACCESSORIES

SMART-CAL Auto Calibration Station Only  
Part # 914-00000-01

Contact SENSIT to discuss calibration kit for Smart-Cal

### Accessories without Pump

Manual Calibration Kit  
Sensit HXG-3 Calibration Kit (2.5% Methane/Air)  
Part # 881-00015

21 liter 2.5% Methane/Air  
Part # 315-080012

221 liter 2.5% Methane/Air  
Part # 315-180013

30" Non-Conductive Probe (Clear)  
Part # 883-00002

2 Piece 30" Non-Conductive Probe  
Part # 883-00003

3 Piece 29" Non-Conductive Probe  
Part # 883-00004

Sensor Cap  
Part # 365-00045

Sensor EX (LEL)  
Part # 375-2611-01

Extension Adapter  
Part # 870-00012

PC Interface with Software  
Part # 870-00008

Printer (Infrared)  
Part # 870-00004

### Accessories with Pump (HXG-3P)

Sensit HXG-3P Calibration Kit (2.5% Methane/Air)  
Part # 881-00016

21 liter 2.5% Methane/Air  
Part # 315-080012

221 liter 2.5% Methane/Air  
Part # 315-180013

Sensor Cap  
Part # 870-00018

Sensor EX (LEL)  
Part # 375-2611-01

Extension Adapter  
Part # 870-00012

PC Interface with Software  
Part # 870-00008

Printer (Infrared)  
Part # 870-00004

For more information, visit [www.gasleaksensors.com](http://www.gasleaksensors.com)



851 Transport Drive  
Valparaiso, IN 46383-8432

Phone: 888 4SENSIT  
888 473 6748  
219 465 2700

Fax: 219 465 2701  
[www.gasleaksensors.com](http://www.gasleaksensors.com)

**MADE IN USA**

SENSIT Technologies  
is in compliance with ISO 9001:2008



Distributed by:

