



**STATIKIL PE**  
Topical anti-stat formulated for PE gas piping

*Excellent visibility on all PE pipes*



**Product available ready for use in:**

- 32 oz spray bottle with simple trigger spray for accurate application.
- 1 Gallon containers

*STATIKIL PE has been tested by independent laboratories and meets or exceeds ASTM D-257-80, MIL B-81705-B, Electronic Industry IS-5 and NFPA-99 specifications for surface resistivity and static decay.*

- Effectively eliminates static charges on PE gas pipe by increasing surface conductivity
- Eliminates need for bulky burlap or pipe wraps
- Keeps work area clear and eliminates trip hazards posed by other grounded pipe “wraps”
- To be used prior to construction operations including squeeze-off, repair, tapping, cutting, venting, etc.
- Colorant added for positive verification of product coverage
- Remains effective even after pipe is dry
- No aerosols. No wasted over spray.

**Specifications**

|                   |  |
|-------------------|--|
| Composition       | High Molecular Weight Topical Antistat                     |
| Physical Form     | Liquid   |
| Color             | Gray Pigment for Visibility                                |
| Flash Point       | None   |
| Freeze Point      | -10° F   |
| Explosion Hazard  | None   |
| Specific Gravity  | 1.0  |
| Odor              | Mild Lemon   |
| pH Regular        | 7.71   |
| Static Decay Rate | MIL-B-81705-B At Relative Humidity @13% 72°F .35 Sec @5 KV |

|                 |                   |
|-----------------|-------------------|
| Health<br>0     | Flammability<br>0 |
| Reactivity<br>0 |                   |



**PLEASE VISIT [WWW.STATIKILPE.COM](http://WWW.STATIKILPE.COM) TO SEE A VIDEO OF STATIKIL PE IN ACTION!**

*Please contact your local distributor with questions or for more information*

MANUFACTURED BY  
**PIPELINE EQUIPMENT RESOURCES COMPANY, LLC**  
[www.perc.us.com](http://www.perc.us.com)