



Reflux 819

Pressure regulator

Classification and Area of Application

REFLUX 819 is a pilot controlled pressure regulator for medium and high pressure applications.

It is particularly suitable for use for the controlling natural gas, for power plants, transmission, distribution, as well as for industrial use.

The Reflux regulators high outlet pressure accuracy of the regulated pressure, the 1,000 to 1 high turndown ratio, and balanced valve design allows fast adaptation to changes in the operating conditions. Even with the presence of abrupt changes in the flow rate, makes the **REFLUX 819** particularly suitable for installations for Gas turbine electric power generation stations Gas Turbine applications.

The **Reflux 819** regulator, is classified as a regulator designed with the valve in the normally closed position (**Fail to Close**).

It is truly a **TOP ENTRY** design, which confers to the regulator management advantages, for example the ability to perform full maintenance without removing the body from the piping.




Fig.1

REFLUX 819 - Basic Version

FEATURES

Functional features:*

■ Maximum inlet pressure:	Up to 1,479 PSIG
■ Range of downstream pressure:	from 4.35 PSIG to 1,073 PSIG depending on installed pilot (see Pilot section).
■ Minimum differential pressure:	7.25 PSIG 30 PSIG fro Reflux FC Worker FO Monitor
■ Minimum ambient temperature:	Used up to - 40°F
■ Maximum ambient temperature:	140°F
■ Inlet gas temperature:	Must be -4°F - 140°F
■ Accuracy class AC:	Up to 1%
■ Lock-up pressure class SG:	Up to 2.5%

Design features:

■ Nominal dimensions DN:	1" ; 2" ; 3" ; 4" ; 6" ; 8" ; 10" ; 12"
■ Flanged connections:	Class 150-300-600 RF or RTJ, according to ANSI B16.5 and PN 16/40 according to UNI 2282 or DIN 2263, (ISO 7005).

Materials:**

■ Body:	Cast steel ASTM A 352 LCC for classes ANSI 600 and 300; Cast steel ASTM A 216 WCB for classes Ansi 150 and PN 16/40.
■ Head covers:	ASTM A 350 LF2 forged steel
■ Stem:	AISI 416 stainless steel
■ Plug:	ASTM A 350 LF2 Nikel coated on sealing surface
■ Seat:	Nitril Rubber Vulcanized on a metal support
■ Diaphragm:	Rubberized canvas (performed by hot-pressing process).
■ Sealing ring:	Nitril rubber
■ Connection fittings:	In zinc-plated carbon steel according to DIN 2353; Stainless steel on request.

REMARK: * Different functional features available on request.

** The materials indicated above refer to the standard models.
Different materials can be provided according to specific needs.

Cg, KG and K1 coefficient

Nominal diameter								
Millimeters	25	50	80	100	150	200	250	300
Inches	1"	2"	3"	4"	6"	8"	10"	12"
Cg flow coefficient	575	2,220	4,937	8,000	16,607	25,933	36,525	55,000
KG flow coefficient	605	2,335	5,194	8,416	17,471	27,282	38,425	57,860
K1 body shape factor	106.78	106.78	106.78	106.78	106.78	106.78	106.78	106.78
								Tab.1

For sizing formulas refer to www.fiorentini.com/sizing

Pilots System

The operation of the **REFLUX 819** is controlled by a pilot system consisting of two separate devices: the **R14/A Pre-regulator** and the **Pilot**.

Preregulator

The following models are available:

R14/A: Is fed by the inlet gas pressure and has a self-adjusting set point. This provides a controlled feeding pressure to the pilot depending on the setting point of the pilot. It is equipped with a built-in filter that is removable and can be cleaned.

R42/A – R44/A – R45/A: equipped with built-in filter on the gas inlet connection (upstream gas), with manually adjustable set point.

Pilot

Reflux 819 regulators are equipped with series **200 pilot**.

The available models, according to the pressure to be regulated, are:

- ☪204/...Outlet pressure control range from 4.35 to 623 PSIG (0,3 to 43) bar (with different setting springs),
- ☪205/...Control range from 290 to 870 PSIG (20 to 60 bar) (with different setting springs),
- ☪207/...Control range from 595 to 1073 PSIG (41 to 74 bar) (with different setting springs).

Pilots are adjusted manually, in the field, or remotely to change the regulated pressure from far away. The following are the various options we offer under the following suffixes:

- ☪.../A Manual setting in place
- ☪.../D Electric/Electronic remote setting control
- ☪.../CS Pneumatic remote setting control
- ☪.../F.I.O. Smart unit for remote setting, monitoring flow limitation and indirect flow measurement

MODULARITY AND ACCESSORIES

The **REFLUX 819** regulator has been designed with a high degree of modularity that allows you to incorporate within the basic regulator the alternative additional accessories. These can also be added to a basic regulator at a later time, with no need to change the existing assembly piping connections.

Incorporated Silencer DB/819

The silencer **DB/819** allows absorbing the noise that is generated in the pressure regulator during the lamination process. Its great efficiency is due to the fact that noise absorption takes place at the same point where it is generated, thus preventing its propagation.




Fig.2

REFLUX 819 - With incorporated silencer

This mechanical solution allows to still have the possibility of incorporating in the basic regulator, besides the silencer, also the slam-shut valve or the monitor.

With the application of the silencer **DB/819** the Cg and KG valve coefficients are 5% lower than the basic regulator.

Slam shut device model SB/82 o HB/97

Slam shuts are **Safety devices** whose task is shutting off the gas flow if abnormal pressure conditions appears, compared to the set point of the installed pressure switch.




Fig.3

REFLUX 819 - With slam shuth SB




Fig.4

REFLUX 819 - With slam shuth HB

The set point can be varied, according to the operating needs, in the ranges referred to in the table N.2, according to the model of pressure switch installed.

The slam shut device is equipped with a button for local manual control of the block operation (this can be deactivated).

The reset of the slam shut, for safety reasons, is exclusively manual, and inside the slam shut, a bypass device is provided in order to make the reset operation easier.

The slam-shut device can be equipped with accessories of pneumatic or electromagnetic type allowing control, as well as with sensors (micro-switches) for the remote signaling of its tripping.

Pressure switch

MOD. SB	MIN.	MAX
102M	2.17 ÷ 40.61	2.17 ÷ 97.17
102MH	40.61 ÷ 79.77	2.17 ÷ 97.17
103M	2.17 ÷ 116.03	26.10 ÷ 333.58
103MH	116.03 ÷ 275.57	26.10 ÷ 333.58
104M	20.30 ÷ 261.06	203.05 ÷ 696.18
104MH	261.06 ÷ 594.65	203.05 ÷ 696.18
105M	29.00 ÷ 638.16	391.60 ÷ 1450.37
105MH	638.16 ÷ 1,305.33	391.60 ÷ 1450.37
MOD. HB		
103	5.80 - 98.62	18.85 - 159.54
104	13.77 - 319.08	145.03 - 456.86
105	36.25 - 725.18	362.59 - 1131.79
105/92	609.15 - 1131.29	797.70 - 1305.33
		Tab.2

Values in PSIG

The slam shut valve can be set for pressure increase, **over pressure shut off (OPSO)** and/or for pressure drop, **under pressure shut off (UPS0)**.

The two set points modes can be adjusted independently, using the dedicated calibration springs: a spring for the intervention of maximum pressure and a second spring for the intervention of minimum pressure.

The choice between the two models - SB/82 and HB/97 - depends on the size of the regulator and on the maximum instantaneous flow rate to be provided.

In general, up to a diameter of 3" (DN 80) you will use the model SB/82; while, for larger sizes, it is necessary to check whether to use the model HB/97 instead of model SB/82.

For sizing, please contact our technical and sales department.

The slam shut device installed in the regulators causes a reduction of the coefficients Cg and Kg equal to about 7% of the value of the basic regulator.

Monitor incorporated PM/819

The **MONITOR REGULATOR** is a safety device whose task is that of performing the functions of the worker regulator in case of failure of the worker regulator.

This is a regulator that is normally in fully open position during normal operation of the worker regulator.

It is generally installed following the gas flow direction, upstream of worker pressure regulator that acts as OPERATING regulator




Fig.5

REFLUX 819 - With monitor incorporated

The Monitor **PM/819** is mounted on the same body of the operating regulator but it is provided with its own sealing seat, pilot system, and an independent motorization.

The functional characteristics of the **Monitor PM/819** are the same of the basic regulator **REFLUX 819**

The assembled **REFLUX 819** with **Monitor PM/819** has a equivalent coefficients C_g and K_G reduced by 7% compared to those of the basic regulator.

This solution allows creating smaller stations featuring very small overall dimensions and lower pressure drops compared to the traditional solution of the two regulators installed in line.

In-line Monitor

In this solution, the Monitor regulator and Worker are installed in series.

Fig. 6 represents the traditional solution where the monitor is usually installed upstream and the worker regulator is installed downstream (following the gas flow direction).

The Monitor regulator is set at a value that is slightly higher than the set point of the Worker regulator.




Fig.6

REFLUX 819 - Solution with in-line monitor

Optional

For the pressure regulators:

- Stroke limiters
- Devices for flow rate limitation
- Limit switches
- Position transmitters
- Stainless steel tubing fittings, dual sealing

For the pilot circuit

- M/A Accelerators
- R14/A/S Pre-regulator for the high pressure circuit ($P > \text{Psi } 174.5$ (12 bar))
- Heating cable for preheating pilot circuit
- Electrical Heater
- Supplementary Filter CF 14
- Dehydrating Filter CF 14/D
- Fluid Control 896, Pilots for modulation of pressure adjustment
- .../F.I.O. SMART unit for remote adjustment

Sizing of pressure Regulator

In general, the choice of a regulator is made based on the calculation of the flow rate determined by the use of formulas and on the flow rate coefficients (Cg or KG) as indicated by the EN 334 standard.
For the proper sizing of the regulators, kindly refer to our website: www.fiorentini.com/sizing.

For different gases and for natural gas with a different density than 0,61 shall be applied the correction coefficients resulting from the following formula:

$$F_c = \sqrt{\frac{175.8}{S \times (273.16 + t)}}$$

S = relative density to air
t = gas temperature [°C]

Correction factors FC		
Type of gas	Relative density (S)	Fc factor
Air	1.00	0.78
Propane	1.53	0.63
Butane	2.00	0.55
Nitrogen	0.97	0.79
Oxygen	1.14	0.73
Carbon dioxide	1.52	0.63

Tab.3

The chart shows the correction factors FC valid for above mentioned gas at 60 °F and to the declared relative density.

Flow rate conversion		
Stm ³ /h	x 0,94795	= Nm ³ /h

Tab.4

CAUTION:

In order to get optimal performance, to avoid premature wear of the regulator components, and to limit noise emissions, it is recommended to check that gas speed at the outlet flanged (this is calculated in the PF sizing program).

The gas speed at the outlet flange may be calculated by means of the following formula:

$$V = 345.92 \times \frac{Q}{DN^2} \times \frac{1 - 0.002 \times Pd}{1 + Pd}$$

where:

- V** = gas speed in m/sec
- Q** = gas flow rate in Stm³/h
- DN** = nominal size of regulator in mm
- Pd** = outlet pressure in barg.

TYPICAL CONNECTION DIAGRAMS

The following examples are provided as a recommendation to get the best performance from the regulator **REFLUX 819**.

IN-LINE INSTALLATION






Fig.7

RECOMMENDED INSTALLATIONS



Standard position

Fig.8



Upside down position

Fig.9

■ Inlet pressure
■ Outlet pressure

■ Motorization
■ Motorization Monitor

■ Control Feed
■ Pilot Feed

RECOMMENDED INSTALLATIONS

Regulator Reflux 819 with incorporated Monitor PM/819




Fig.10

Slam Shut SBC 782 and Reflux 819 pressure regulator with incorporated slam shut device SB82




Fig.11

Monitor Reflex 819 with incorporated slum shut HB/97 and operating pressure regulator Reflex 819




Fig.12

Pressure regulator operating monitor Reflex 819 and operating pressure regulator Reflex 819




Fig.13

REFLUX 819





Fig.14

Dimensions								
Inches	1"	2"	3"	4"	6"	8"	10"	12"
S - Ansi 150/PN 16	7.25	10.5	11.75	13.88	17.75	21.38	26.5	29.01
S - Ansi 300	7.75	11.25	12.5	14.5	18.62	22.38	27.88	30.51
S - Ansi 600	8.25	13.78	13.25	15.5	20	24	29.62	32.24
A	12.60	5.11	16.92	19.29	25.60	29.52	31.49	37.40
B	3.93	10.95	5.9	7.48	8.85	10.43	13.38	14.67
C	10.94	6.30	14.17	14.17	20.07	20.07	24	28.27
E	12.20	12.20	12.60	12.59	16.53	16.53	18.5	19.68
F	10.24	16.92	13.77	14.96	16.14	18.11	22	25.39
H	16.53	7.87	22.83	26.77	34.44	39.96	48.81	51.18
P	6.69	200	10.23	11.41	12.59	14.56	19.68	24.80
								Tab.5

Pneumatic fittings; 1/4"NPT

Dimensions S according to EN 334 and IEC 534-3

Weight in Lbs								
Ansi 150/PN 16	97	134.4	231.5	321.8	679	899.5	1,984	2,543.1
Ansi 300	99.2	136.7	240.3	344	760.5	1,036	2,094	3,108.5
Ansi 600	101.4	141	246.9	363.7	793.6	1,091	2,204	3,284.9
								Tab.6

REFLUX 819 + SB/82 + HB/97

Fig.15
Dimensions

Inches	1"	2"	3"	4"	6"	8"	10"	12"				
S - Ansi 150/PN 16	7.25	10	11.75	13.88	17.75	21.38	26.5		29.01*			
S - Ansi 300	7.75	10.5	12.5	14.5	18.62	22.38	27.88		30.51*			
S - Ansi 600	8.25	11.25	13.25	15.5	20	24	29.62		32.24*			
A	12.59	13.77	16.92	19.29	25.59	29.52	31.49		36.53*			
B	8.46	9.44	10.62	11.81	20.39*	14.76	25.39*	17.71	27.04*	20.86	31.33*	37.00*
C	10.94	10.94	14.17	14.17	20.07	20.07	24.01		28,24*			
E	12.20	12.20	12.59	12.59	14.09*	16.53	16.14*	16.53	17.51*	18.5	20.07*	20.96*
F	10.23	11.41	13.77	14.96	16.14	18.11	22.04		25.35*			
H	21.06	23.22	27.55	31.1	40.35	47.24	52.36		73.22*			
P	6.69	7.87	10.23	11.41	12.59	14.56	19.68		24.80*			

Tab.7

Pneumatic fittings: 1/4 NPT

* Weight & dimensions with HB/97.

Dimensions S according to EN 334 and IEC 534-3.

Weight in Lbs

Ansi 150/PN 16	116.8	156.5	253.5	352.7	705.5	1,014	2,094		3,560.5*			
Ansi 300	121.2	161	269	377	394.6*	804.5	895*	1,157	1,230.1*	2,204	2,378.7*	3,725.8*
Ansi 600	123.4	165.5	275.5	397	434.3*	837.7	952.3*	1,212.5	1,287.4*	2,314	2,422.8*	3,902.2*

Tab.8

REFLUX 819 + PM/819





Fig.16

Dimensions							
Inches	1"	2"	3"	4"	6"	8"	10"
S - Ansi 150/PN 16	7.25	10	11.75	13.88	17.75	21.38	26.5
S - Ansi 300	7.75	10.5	12.5	14.5	18.62	22.38	27.88
S - Ansi 600	8.25	11.25	13.25	15.5	20	24	29.62
A	12.59	13.77	16.92	19.29	25.59	29.52	31.49
B	12.59	13.77	16.92	19.29	25.59	29.52	31.49
C	10.94	10.94	14.17	14.17	20.07	20.07	24.01
E	12.2	12.2	12.59	12.59	16.53	16.53	18.5
F	12.23	11.41	13.77	14.96	16.14	18.11	22.04
H	25.19	27.55	33.85	38.58	51.18	59.05	63
P	6.69	7.87	10.23	11.41	12.59	14.56	19.68
							Tab.9

Pneumatic fittings: 1/4" NPT

Dimensions S according to EN 334 and IEC 534-3

Weight in Lbs							
Ansi 150/PN 16	185	231.5	296.7	540	1,139.7	1,477	3,086.5
Ansi 300	187.3	233.7	405.7	562.2	1,221.5	1,611.5	3,196.7
Ansi 600	189.5	238	412.2	582	1,254.5	1,666.7	3,307
							Tab.10

REFLUX 819 + DB/819

Fig.17
Dimensions

Inches	1"	2"	3"	4"	6"	8"	10"	12"
S - Ansi 150/PN 16	7.25	10	11.75	13.88	17.75	21.38	26.5	29.01
S - Ansi 300	7.75	10.5	12.5	14.5	18.62	22.38	27.88	30.51
S - Ansi 600	8.25	11.25	13.25	15.5	20	24	29.62	32.24
A	20.47	22.63	27.55	31.49	36.81	42.71	51.18	59.25
B	3.93	5.11	5.9	7.48	8.85	10.43	13.38	14.64
C	10.94	10.94	14.17	14.17	20	20	24	28.26
E	12.2	12.2	12.59	12.59	16.53	16.53	18.5	13.58
F	16.73	19.48	24.21	26.37	31.29	35.23	4.33	48.63
H	24.4	27.75	33.46	38.97	45.66	53.14	64.56	73.99
P	14.56	15.74	19.88	23	27.16	30.31	39.37	47.44
K	8.66	11.81	13	15.35	18.89	23.42	27.36	29.33

Tab.11
Pneumatic fittings: 1/4 NPT

Dimensions S according to EN 334 and IEC 534-3

Weight in Lbs

Ansi 150/PN 16	154.3	277.7	430	573.2	1,245.7	1,841	2,822	2035
Ansi 300	158.73	282.2	449.7	673.1	1,340	2,039	3,042.5	1230
Ansi 600	161	286.6	456.3	657	1,411	2,093.5	3,152.5	2310

Tab.12

REFLUX 819 + DB/819+SB/82+HB/97




Fig.18

Dimensions

Inches	1"	2"	3"	4"	6"	8"	10"	12"				
S - Ansi 150/PN 16	7.25	10	11.75	13.88	17.75	21.38	26.5		29.01*			
S - Ansi 300	7.75	10.5	12.5	14.5	18.62	22.38	27.88		30.51*			
S - Ansi 600	8.25	11.25	13.25	15.5	20	24	29.62		32.24*			
A	20.47	22.63	27.55	31.49	36.81	42.71	51.18		59.25*			
B	8.46	9.44	10.62	11.81	20.39*	14.76	25.39*	17.71	27*	20.86	31.33*	37.00*
C	10.94	10.94	14.17	14.17	20	20	24		28.26*			
E	12.2	12.2	12.59	12.59	14.09*	16.53	16.14*	16.53	17.51*	18.5	20.07*	20.86*
F	16.73	19.48	24.21	26.37	31.29	34.05	43.30		48.03*			
H	28.93	32.08	38.18	43.3	51.57	60.43	72.05		96.25*			
P	14.56	15.74	19.88	22.63	27.16	30.31	39.37		47.44*			
K	8.66	11.81	13	15.35	18.89	23.42	27.36		29.33*			
												Tab.13


Pneumatic fittings: 1/4" NPT

* Weight & dimensions with HB/97.

Dimensions S according to EN 334 and IEC 534-3.

Weight in Lbs

Ansi 150/PN 16	174.16	300	452	604*		1,272*	1,955.5*	2,932				5,103.6*
Ansi 300	180.77	306.5	478.5	670.5*	701.5*	1,384.5	1,457*	2,179.5*	2,217.9*	3,152.5	3,882.3*	5,518.2*
Ansi 600	183	311	485	690.5*	727.5*	1,455	1,514.5*	2,275.1*	2,275.1*	3,263	3,926.4*	5,709.3*
												Tab.14

REFLUX 819 + DB/819 + PM/819

Fig.19

Dimensions							
Inches	1"	2"	3"	4"	6"	8"	10"
S - Ansi 150/PN 16	7.25	10	11.75	13.88	17.75	21.38	26.5
S - Ansi 300	7.75	10.5	12.5	14.5	18.62	22.38	27.88
S - Ansi 600	8.25	11.25	13.25	15.5	20	24	29.62
A	20.47	22.63	27.55	31.49	36.81	42.71	71.20
B	12.59	13.77	16.92	19.29	25.59	29.52	44.20
C	10.94	10.94	14.17	14.17	20	20	24
E	12.2	12.2	12.59	12.59	16.53	16.53	18.5
F	16.73	19.48	24.21	23.37	31.29	35.23	43.3
H	33.07	36.41	44.48	50.78	62.4	72.24	82.67
P	14.56	15.74	19.88	22.63	27.16	30.31	39.37
K	8.66	11.81	13	15.35	18.89	23.42	27.36

Tab.15

Pneumatic fittings: 1/4" NPT

Dimensions S according to EN 334 and IEC 534-3.

Weight in Lbs							
Ansi 150/PN 16	242.5	374.8	595.3	791.5	1,706.5	2,418.7	3,924.5
Ansi 300	247	379.2	588.5	855.4	1,726.2	2,612.5	4,144.7
Ansi 600	249.2	383.7	595.2	875.5	1,796.7	2,667.5	4,255

Tab.16

www.florentini.com

The data are not binding. We reserve the right to make changes without prior notice.

