












Standard-Seal Only Couplings

| Product | Product Type | Pipe Sizes | Lengths | Gaskets | Finish |
|---|--|--------------------------|-----------------------------------|---|--------------------|
|  E Series | IPS Steel Pipe | 1/2" and up IPS | 5", 7", 12", 16" and 24" standard | Plain or conductive | Shop coat or epoxy |
|  E Series | Insulating IPS Steel Pipe | 3/4" thru 48" IPS | 5", 7" and 16" standard | One insulating, one conductive | Shop coat or epoxy |
|  E Series | Cast Iron | 2.50" thru 48" OD* | 5", 12" and 16" | Plain | Shop coat or epoxy |
|  E Series | Reducing, IPS, Steel Pipe | 2" to 1 1/4" and up | 7" and 10" | Plain or conductive | Shop coat or epoxy |
|  E Series | Insulating, Reducing, IPS Steel Pipe | 2" to 1 1/4" and up | 7" and 10" | One insulating, one conductive | Shop coat or epoxy |
|  E Series | Reducing, CI to IPS Steel Pipe | 2.5" CI to 2" IPS and up | 7", 12" and 16" standard | One insulating, one conductive | Shop coat or epoxy |
|  EB Series | Vented Line Cap, IPS Steel Pipe | 1 1/4" and up | 5" standard | Plain or conductive | Shop coat or epoxy |
|  EB Series | Vented Line Cap, Cast Iron | 2.50" and up | 7" standard | Insulating from pipe, conductive from cap | Shop coat or epoxy |
|  E-UFA Series | Standard, Seal Only - Flanged Adapters** | 2" and up | 12" standard | Conductive | Shop coat or epoxy |

*Larger sizes available

**150# and 300# Flange mating

Rod & Lug Harness Device for Steel Pipe



Light Duty: 3/4" x 18", 24", 30" or 38"
Heavy Duty: 7/8" X 24", 30" or 44"
Finish: Shop coat epoxy
Lugs/Bushings: Conductive both ends or insulating one end.

Lugs & Bushings also available seperately.

Special Note

The couplings on this page do not restrain the pipe. If pipe pull-out is a possibility, use the Rod and Lug Harness Device.

The Maxi-Grip Couplings have seal and restraint capabilities.